




Specifications

OT26-12(W)		
Nominal Voltage	12V	
Rated Capacity (20 hours rate)	26Ah	
Dimension (± 2 mm)	Total Height (with terminals)	125mm
	Length	175mm
	Width	165mm
	Height	125mm
Weight (Approx)	8.05Kg	


Characteristics

Capacity	20 hours rate	(1.3A)	26Ah
Discharge Current Testing (25°C)	20 I ₂₀ rate 1	(26A, 27min)	34min
	60 I ₂₀ rate 3	(78A, 7min)	8min
Internal Resistance	Full Charged Battery 25°C		10mΩ
Capacity Affected By Temperature (20 hours rate)	40°C		102%
	25°C		100%
	0°C		85%
	-15°C		62%
Residual Capacity (25°C)	Capacity After 3 Months Storage		91%
	Capacity After 6 Months Storage		82%
	Capacity After 12 Months Storage		64%
Cycle (Above 300 Time)	Discharge 2hrs at 6.5A Current Charge 6hrs at 2.6A Current (25°C)		
Charge (Constant Voltage)	Cycle (25°C)	Initial Charging Current Less Than 7.8A; Voltage 14.5~14.9V	
	Float (25°C)	Charge Voltage 13.6~13.8V	

★ The above are average and data obtained from the first 3 charge/discharge cycles. These are not minimum values.



Discharge Current & Duration Time



Discharge Current 25°C

